



 GERMAN  
ENGINEERED

# Novoferm Insulated Roller Garage Doors



*Intelligent Door Solutions*



[www.novoferm.co.uk](http://www.novoferm.co.uk)


# Our Story

Novoferm are proud to be a part of the Sanwa Holding Corporation, founded in 1986 and today, considered to be a major global player in the access systems industry.

Sanwa conduct business in 25 countries and regions worldwide with a strong presence in Japan, North America, and Europe.

At Novoferm, we are building a team and giving them the support to achieve our ambitions. We will continue building on the improvements and investments that have already begun to improve lead-time reliability and quality for all our clients.

Our vision is to lead through organic business improvement, investment, digital enablement, and tuck-in acquisitions.



# Contents

We'll find the right solution for you and see that it is tailored to your exact requirements. Whether you're building a new garage or renovating an existing one, you'll find that our incredible selection of doors are always the right choice.



Introduction & Benefits	4-5
Novorol Security	6
Novorol Roller Doors	7
Novorol Colours	8
Novorol 77 Features	9
Novorol 55 Features	9
Insulation	11
Accessories	13
Warranty and Maintenance	14
Terms and Conditions	15



*Intelligent Door Solutions*

# Novorol Roller Doors



SCAN TO SEE MORE DETAILS



# Discover the benefits of a Novorol Door

## Automation

The complete range of automatic doors listed in this brochure can be operated remotely with one of our tamper-proof hand transmitters. Alternatively, you can choose from one of our handy remote switches.

Our range of insulated roller doors come loaded with features such as lighting control and built-in security protection. Plus, our control system can work in tandem with our smartphone app for maximum convenience.

## Space-Saving

Our insulated roller doors open vertically, unlike up and over doors that swing outward, so you can use every inch of your driveway.

## Security

Our garage doors come fully automated, so there is no lock to pick. Anti-thief features give further protection against unauthorised entry and an integral courtesy light illuminates the garage interior.

Plus, our doors come with other security features, from a built-in emergency sensor to a self-locking motor.

## Colours

Our doors are available in an array of eye-catching colours, with options to suit any preference and the period and aesthetics of your home.



## Wood Effect/Finishes

Woodgrain finishes are available.

## Insulation

Premium insulation keeps your property warm and dry in the winter and cool in the summer. It can also help with dampening external noises.

# Security Features

## Novoferm Patented Security

→ The combination of side runners and auto-positive locking with anti-lift geometry locking straps makes the Novorol extremely secure.

### Manual Override

A connector and crank handle are supplied as standard, so your door can be opened, from inside, even during a power cut.

### Guide Rails

Guide rails made from aluminium profile, colour matched as standard.

### Safety Edge

Supplied as standard. At the bottom edge of your door is an emergency sensor which will stop and reverse when the door is in operation, if it senses an obstruction.

### NovoShield

Supplied colour matched as standard, shields the user from accidental finger entrapment and provides an attractive finish to the door curtain.

### Control System

An interior light is provided within the self contained control box.



## Vision slats allow natural light into your garage

Polycarbonate clear glazing option is available on a proportion of the door curtain on the Novorol 77 only.



SCAN TO SEE MORE DETAILS

# Novorol Roller Doors

**The Novorol combines a space saving design with the convenience of an electrically operated automatic door.**

The door lifts vertically and rolls into a box at the head of the garage door opening, providing more space in front of the garage. This allows you the option to park closer as the door does not swing out like a traditional garage door, which is ideal if you have a shorter driveway. This unique design also allows you more space inside the garage for storage etc.

The Novorol door is available in an array of colours and finishes, with vision laths available should you need to allow in more light.

Space-saving Novorol roller doors are safety certified to EN12453 and fitted with NovoShield and a safety edge as standard.

## No other door is quite like Novorol

Novorol takes the concept of the roller garage door to a new level. It out-performs the ordinary garage door for ease of use, insulation, finishes, safety and security plus all doors are manufactured under ISO 9001 quality guidelines.

Two designs are available - the Novorol 77 which is the ultimate in remote control luxury, and the ultra-compact Novorol 55, the solution for tight spaces, which is available in the remote control version.

Novorol 77 doors require only 300mm of head room space and open vertically. The Novorol 55 requires only 205mm of headroom and is available up to 3 metres wide and 2.286metres high.



WARRANTY COVER



MADE TO MEASURE



REMOTE AS STANDARD



SECURITY LOCKING

# Colours

The colourful choice of finishes can provide either an accent or a complement to existing finishes.

## Standard Colours



A choice of 13 stunning textured steel finishes available in our most popular standard colours.

Traffic White RAL 9016	Jet Black RAL 9005	Anthracite Grey RAL 7016	All colour samples depicted in this brochure are as close to the original manufacturer's colours as possible. Garage doors supplied may vary in colour from the brochure representation.	
Chartwell Green BS4800	Blue RAL 5011	Rosewood	Racing Green RAL 6009	Golden Oak
Agate Grey RAL 7038	Brown RAL 8014	Burgundy RAL 3004	Mocca RAL 8019	Cream RAL 9001

## Elite Colours



A choice of 2 stunning colours in a textured steel finish available in a brand new exciting colour range for those who want something a little more special!

Golden Oak	Rosewood	High Grade Woodgrain Laminate Finishes
------------	----------	--







### Novorol 77 door features:

- Standard White Polyester Painted 70mm Guides up To 3m Wide (Colours available)
- Standard White Polyester Painted 90mm Guides over 3m Wide (Colours available)
- Optional White 300mm NovoShield Full Box (Other Box Options Available)
- Novorol Hard Wired Control Safety System
- Two 2-Channel Hand Transmitters

### Novorol 55 door features:

- Standard White 65mm Guides (Colours Available)
- White 205mm NovoShield Full Box (Colours Available)
- Novorol Hard Wired Control Safety System
- Two 2-Channel Hand Transmitters



WARRANTY COVER



MADE TO MEASURE



REMOTE AS STANDARD



SECURITY LOCKING



The clean lines of the Novorol door are attractive in any setting



## Automatic Safety Features

Automatic safety features will stop and reverse the door operation when it senses an obstruction.

Frame and door weather seals help keep the rain and wind out.

Optional LED lighting kits will show off your door's best features and help with security.

## Built-in Insulation

Insulated foam filled laths, which provides both a thermal and acoustic barrier, helping to control your energy bills, reduce noise and possibly your carbon footprint.

# Novorol Insulation

Our automated insulated Roller doors are constructed from 77mm or 55mm double walled aluminium laths filled with CFC free insulating foam, an ideal solution for those who want to improve the appearance and gain space in their garage.

Known as Novorol 77 and 55 these insulated roller doors are strong and efficient.

Novorol is a feature packed insulated roller door which comes with a full box and 70mm guides up to 3m or 90mm guide for doors over 3m as standard. The Novoferm Novorol is one of our bestselling roller doors. Homeowners love that they can have an automatic door with no ceiling tracks or operator boom.

The fact that you can drive right up to the door and park there, means it is fantastic a space spacing option that maximises drive-through width.

## Features

- ✓ The insulated aluminium laths provide a thermal and acoustic barrier, which could reduce your energy bills, reduce your carbon footprint and provide noise reduction
- ✓ ISO 9001 quality standard
- ✓ Virtually maintenance free



WARRANTY COVER



MADE TO MEASURE



REMOTE AS STANDARD



SECURITY LOCKING





# Accessories

You'll need the right accessories to go with the hardware of your choice



SCAN TO SEE MORE DETAILS

## Hand transmitters



Mini-Novotron 522 Design hand transmitter  
2-channel, 433 MHz, KeeLoq rolling code



Mini-Novotron 524 Design hand transmitter  
4-channel, 433 MHz, KeeLoq rolling code



Mini-Novotron 522 hand transmitter  
2-channel, 433 MHz, KeeLoq rolling code



Mini-Novotron 524 hand transmitter  
4-channel, 433 MHz, KeeLoq rolling code

### Wireless

### Wired



Signal 111 remote wall switch  
2-channel, 433 MHz, KeeLoq rolling code for controlling 2 operators or 1 operator and 1 outside lighting in UV-resistant material



Signal 218 remote coded key pad  
10 codes, 433 MHz, KeeLoq rolling code with stainless steel cover, backlit in UV-resistant material



Signal 112 wall switch  
Start key, holiday switch, continuous light (On/ Off), 24 V connection to the operator in UV-resistant material



Coded key pad signal 213  
3 signals, metal key pad, 230 V connection

# Warranty and Maintenance

## Our Promise

During the warranty period, we undertake to rectify any defects to the Novoferm product, which can be proven to be attributed to a material or manufacturing defect.

We promise, at our discretion, to either exchange the defective merchandise or repair it.

Replacement parts remain our property.

## What is Covered

- 5 years – Motor
- 5 years – Control Unit
- 2 years – Remote Controls and Accessories (excluding batteries, bulbs, and fuses)
- 5 years – Lath Finish
- 2 years – Movable and Mechanical Parts (including but not limited to locking straps and rings, safety brake.)

## Lath Finish

Our roller doors come in two finishes: a polyester powder coat and a woodgrain laminate. Weathering and sun exposure can cause the laths to fade. We guarantee the finish for five years and that any fading will be minimal and uniform, providing the door is maintained in accordance with the care and maintenance advice.

## Corrosion

Doors situated in 'high corrosive' areas such as within three miles of the sea, or a large body of saltwater, are not covered for rust or corrosion of steel parts. Cleaning of the doors is especially important in these locations.

## Warranty Requirements

This warranty only covers damage to the purchased garage door or garage door operator. A visual standards check will need to be carried out. You will also be required to show a fully completed warranty service passport (service to be conducted by a qualified engineer annually), together with a receipt of purchase, which correspondingly substantiates your right to claim under warranty. The finish on doors is exempt from the service requirements. In the event of a claim, please contact the company that

supplied/ installed the doors. They will raise the warranty on your behalf.

Please note that due to the rolling action of the door, surface marking can be caused by security locks, dust and debris. This does not constitute a product fault, and performance is not affected in any way.

During the claims process, a site inspection may be required. For this, we will send an independent assessor. Should this inspection indicate the fault was not caused by a manufacturing defect, you will be liable for the cost of a non-warranty call out. The cost of the call out will be advised prior to the arranged visit.

Novoferm will not accept consequential costs for installation or de-installation, the inspection of parts, transport, and postage costs.

## Care and Maintenance

Your door should be kept clean with any stains removed as soon as possible. You should also ensure that the door does not come into contact with any caustic or acidic substance which could damage the door surface or structure. Your door should be cleaned thoroughly approximately every 2-3 months (in coastal areas or areas close to large bodies of saltwater, this should be done weekly) using warm water and a soft cloth or sponge. Allow the door to dry naturally. Never use detergent, abrasive, caustic, or solvent-based cleaners. With roller doors, it is particularly important to keep the doors clean due to the nature of a roller; any soiling can rub on the laths, causing damage.

Ensure that the guides are clear and free from debris, allowing continual smooth operation. Do not operate the door when not within visual range.

## What is not Covered?

- Improper installation, negligent care and maintenance - doors that have not been maintained or had annual maintenance/ servicing
- Improper initial and subsequent operation
- Negligent or wanton destruction
- External influences, such as fire, water, salts, alkaline solutions, acids, and any abnormal environmental influences, sunlight

- Mechanical damage, through improper transport and fitting, or through falling or hitting objects
- Repair by non-qualified persons
- Using non-Novoferm parts without the written approval of the manufacturer
- Removal of the product number, or making it unidentifiable
- Application of additional, non-approved weights or infills
- Failure to remove the protective film or packaging provided with the product, where applicable
- Failures caused by extreme or abnormal weather conditions

## Extreme Weather Conditions

In extreme heavy storms, laths could be susceptible to water ingress. Also, during gale force winds where the door is positioned within full force of the wind, there is a possibility of the door curtain being blown inwards/ out of the doors' guides.

## Visual Standards Check

A visual standards check must be carried out prior to a warranty submission. This check should be carried out in natural daylight, not direct sunlight, standing at a distance of 3m from the door to view the overall appearance. Doors are acceptable if the following are not readily visible on the face of the door:

- Marks or distortion associated with the manufacturing process
- Minor indentations, marks, or scuffs on the surface
- Paint or stain blemishes

Full full details on our warranty and maintenance, please visit [www.novoferm.co.uk/installation-warranty-and-maintenance-details/](http://www.novoferm.co.uk/installation-warranty-and-maintenance-details/)

# Terms and Conditions

## Warranty

In the unlikely event of a warranty claim becoming necessary please contact the dealer or distributor who supplied the door.

To enable your claim to be processed without delay you should provide the following information:

- Your name, address and contact telephone number
- The original invoice and date of purchase
- A description of the door, the door type and the product number
- A description of the reason for the claim

Your dealer will then supply details of your claim, together with a copy of the warranty card supplied with the door and proof of purchase, to the warranty department at Novoferm UK.

An assessment of the claim will be made. This may mean Novoferm will need to come and inspect your door at your premises.

In the event that there is no legitimate claim under the terms of the warranty you will be liable for the costs of this visit. It is essential that you take note of the care and maintenance instructions provided with your door and you follow these instructions throughout the lifetime of your door. It is essential that you take note of the care and maintenance instructions provided with your door and you follow these instructions throughout the lifetime of your door.

The warranty does not cover:

- Improper installation
- Normal wear and tear
- Priming and other surface protection treatments
- Negligent or wanton destruction
- Incorrect or too late applied surface protection treatments
- Repair by a non-qualified installer
- Use of non-Novoferm parts without the approval of Novoferm
- Damage or removal of the product number or making it unidentifiable
- Improper operation
- External influences, such as fire, salts, water, sun, alkaline solutions, abnormal environmental influences
- Mechanical damage caused by improper transport or installation

All dark colours which are exposed to direct sunlight should be avoided. Dark coloured doors may undergo expansion

due to heat absorption. Such instances are not covered by the guarantee, however normal performance will revert when the door has cooled down if the heat absorption has affected the door's performance.

All colour samples depicted in this brochure are as close to the original manufacturer's colours as possible. Garage doors supplied may vary in colour from the brochure representation.

## Prices

All orders are accepted on the understanding that the goods will be subject to the prices ruling at the time of delivery, unless other terms are specifically agreed. All prices are in £ sterling and exclude VAT.

A 25% handling charge applies to all unwanted items on standard stock items only. Items must be returned unopened and in an unused condition.

All returns are subject to acceptance by Novoferm UK Limited.

## Specification

Due to the progressive outlook of the Novoferm Group we reserve the right to alter specifications to design and manufacture without notification. All specifications and details are correct at the time of publication, errors and omissions excepted.

## All Doors

**Colour match** Pairs of doors should be ordered together to obtain the best colour match, bearing in mind the limitations of the materials used in the construction.

**Size variations** As the size of a door changes in height and/or width, the panel frequency and profile can change, therefore doors of the same style but of different sizes can be significantly different in appearance.

## Right to Cancel

Any bespoke product which is made to measure/customised, is exempt of any cancellation rights.



Your Novoferm Stockist



*Intelligent Door Solutions*



Call Us Now +44 (1582) 563777

Opening times  
8.30am - 5.00pm  
Monday to Friday

Novoferm UK  
Unit 5 - 9 North Luton Industrial Estate  
Sedgwick Road  
Luton  
LU4 9DT  
E: [customerservice@novoferm.co.uk](mailto:customerservice@novoferm.co.uk)  
[www.novoferm.co.uk](http://www.novoferm.co.uk)